

RUBBER GROMMETS

These are made of hard-wearing EPDM rubber which can handle exposure to oils and withstand temperatures up to 120 °c. These are commonly used for protecting conduits that pass through holes in steel or wooden panels.

Available sizes (grommet hole x panel hole x panel thickness)

Size	Code	Size	Code
#1 3.9x7.9x1.6mm	1344	#17 62x66.6x1.6mm	1335
#2A 4.8x10x1.6mm	1333	#18 28.5x38.1x1.6mm	1334
#2B 4.8x12x1.6mm	1332	R205 7.9x12.7x1.6mm	1322
#3 6.4x11.1x1.6mm	1331	R67 14.2x22.2x5.5mm	4088
#3A 6.4x11.1x3.6mm	1330	6.3x3.4x1.6mm	3784
#4 9.5x12.7x1.6mm	1329	9.5x4.8x1.6mm	4043
#4A 9.5x12.7x3.2mm	1328	12.7x7.9x1.6mm	4042
#5 6.4x14.2x1.6mm	1327	15.9x13.5x1.6mm	4047
#6 9.5x19x1.6mm	1326	22.2x19x3.2 mm	3782
#7 15.9x20.6x1.6mm	1325	25.4x19x1.6mm	4033
#8 12.7x19x1.6mm	1324	28.6x25.4x1.6mm	4048
#9 15.8x25.4x1.6mm	1323	38x32x1.6mm	10267
#11 11.1x17.4x1.6mm	1343	Gang12.7x9.5x6.3x3mm	4057
#11A 11.1x15.8x1.6mm	1509	J 17.5x11.1x7.9x1.6mm	4044
#11B 11.1x17.4x4.8mm	1342	Top Hat 13mm	4115
#12 25.4x33.3x1.6mm	1341	Top Hat 19mm	4117
#13 19x22.2x1.6mm	1340	Skydome Small	4088
#13A 19x25.4x3.2mm	1339	Skydome Large	4087
#14 20.6x33.3x1.6mm	1338	Curved 19mm	11985
#15 54x63.5x1.6mm	1337	Water Cylinder	1308
#16 31.7x38.1x1.6mm	1336		



Grommet, top hat grommet



J grommet, curved grommet



Sky dome, water cylinder grommet

RUBBER BODY PLUGS

Also known as blind or blanking grommets. Made of hard-wearing EPDM rubber so it can handle exposure to oils and temperatures up to 120°C. These are commonly used for plugging holes in steel panels. Suited to fit a 1.6mm thick panel.

Available sizes:

Size	Code	Size	Code
6.3mm	4057	22.5mm	1356
7.9mm	1351	25.4mm	1355
9.5mm	1350	28.6mm	1354
12.7mm	1359	32mm	1353
15.9mm	1358	38mm	1352
19mm	4049	51mm	3780
19.1mm	1357		

